

Water heating fireplace MBO left 15 kW Ø 200

MBO/PW/15/L/BS/W EAN: 5901350032886 MBO/PW/15/L/BS/W/BLACK EAN: 5901350032909

BGN 6329

The double glass inserts of the MBO PW line are an economical and ecological solution with a water-based unit, which does not differ from a the typical air insert. Thanks to the unusual vision of the fire and the delicate frame, it perfectly fits into the design of modern interiors.





TECHNICAL DATA

| N | _ | | | | | | |
|----------|---|---|---|---|---|---|---|
| | G | 6 | n | ρ | ٢ | a | ı |

| Rated output (kW) | 15 |
|--------------------------------|----------|
| Heating power range (kW) | 6.0 - 18 |
| Average power from water (kW) | 8 |
| Heating efficiency (%) | 83 |
| Max working pressure (bar) | 2 |
| Material | steel |
| Exhaust gas temperature (🛚) | 210 |
| Max length of logs (cm) | 50 |
| Water capacity (l) | 42 |

Physical parameters

| Weight (kg) | 271 |
|------------------------------|------|
| Width (cm) | 91 |
| Height (cm) | 134 |
| Depth (cm) | 57.5 |
| Exhaust outlet diameter (mm) | 200 |

Efektywność Energetyczna

| Energy class | A+ |
|--|-------|
| CO emissions (at 13% O 2) ≤ given in % | 0.1 |
| Dust emission (mg/Nm3) | 7 |
| Energy efficiency index | 109.3 |

Certyfikaty/Zgodność

Certifications / Compliance Compliance with BIMSCHV 2, Designed for recuperation, KRATKI PRO, Meets the criteria of eco-project





(EEI)

Equipment

Equipment

Air intake, Decorative glass glass, Loading the combustion chamber



