

Steel fireplace NBU left right 11 kW Ø 200 Lift-up

NBU/500/700 EAN: 5901350034415

NBU/500/700/BLACK EAN: 5901350034422

BGN 10179

Three-sided glazed NBU insert has unique aesthetic and exceptional functionality. Apart from visual effects, the insert guarantees efficient heating and ecological wood combustion.



TECHNICAL DATA

General

Rated output (kW)	11
Heating power range (kW)	4.5 - 14
Heating efficiency (%)	83
Exhaust gas temperature (°C)	180
Material	steel
Fuel type	seasoned hardwood (moisture ≤20%)
Max length of logs (cm)	50
Min outlet grids active field (cm ²)	≥900
Min inlet grids active field (cm ²)	≥700
Glazing type	corner

Efektywność Energetyczna

Energy class	A+
Energy efficiency index (EEI)	111.4
CO emissions (at 13% O ₂)	0.09

Physical parameters

Weight (kg)	299
Width (cm)	57.8
Height (cm)	147.1
Depth (cm)	102
Exhaust outlet diameter (mm)	200

Certyfikaty/Zgodność

Certifications / Compliance

Compliance with BIMSCHV 2, Designed for recuperation, KRATKI PRO, Meets the criteria of eco -project

2) ≤ given in %

Dust emission (mg/Nm ³)	17
--	----

► Equipment

Equipment

**Air intake, Ashpan,
Decorative glass glass,
Loading the combustion
chamber**

